



Available with automatic control as standard or optional mechanical timer (as shown).




Ferroresonant Charger

This automatic control charger is perfect for charging several different battery sizes and configurations. The CCL charger is a universal ferroresonant charger with a constant current to the battery of 28 amps. Input voltage is 120/1/60 and draws a maximum of 15 amps ac so it can be plugged into any standard wall outlet. Also available in other AC voltages.

Standard Control V1046371

Features



- Available with standard fully automatic control or optional mechanical timer
- Portable (models with cart)
- Improved Serviceability
- Standard control - Charge 3 to 24 cells
- Optional Control - Charge 1, 2, 3 or up to 24 cells

GNB
INDUSTRIAL POWER
A Division of Exide Technologies

CC
Constant Current
Ferroresonant Series

EF
Ferroresonant Series

GNB[®] Industrial Power CC Series Constant Current Ferroresonant Industrial Charger

Description

This versatile charger has the ability to maintain a constant DC output current (+/- 1% at nominal line voltage); regardless of the number of cells connected (to 24 cells). It is an ideal purchase choice for situations where several batteries of different cell and amp-hour sizes are being charged.

Ideal for Rental Fleets and as a Loaner

There are several applications such as: rental fleets, service loaners, and shop applications that make this a real money saver. It's no longer necessary to stock all the variations of charger sizes that tie up money, or cause you to deal with logistics issues. This unit will provide the maximum output current possible from a 120 volt / 15 amp receptacle.

Models

- CCS2/24-28C1 (Charger with Standard Control)
- CCS2/24-28C1MT (Charger with Mechanical Timer Control)
- LS2/24-28C1 (Charger with Standard Control and Wheeled Cart)
- LS2/24-28C1MT (Charger with Mechanical Timer Control and Wheeled Cart)

Specifications

- 120 VAC input, 15 amps maximum AC line draw
- Fixed output current of 28 amps DC for up to 24 lead-acid cells
- Weight: 120 lbs. including cart
- Overall dimensions: 36"H, 27"W, 17-3/4"D
- Control: Mechanical timer (Settable for 16 hour maximum charge)
- AC power cord: 8-foot of 14/3 SJTOW cord w/molded 15-amp plug
- DC cables: 10-foot
- Connector: SB 175 gray connector
- Optional connector: Dual plug w/HD guard (175/350) PN V10038199
- UL cUL Listed

GNB Industrial Power

USA - Tel: 877.462.4636

Canada - Tel: 800.268.2698

www.gnb.com

GB4176 2014-09

Note: Design and/or specifications are subject to change without notice. If questions arise, contact your local sales representative for clarification.